

AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions and listings of claims in the application:

LISTING OF CLAIMS:

1. (original): A recording method comprising:

a step of changing a carry command value, when carrying a recording medium, according to a state of bending of said recording medium that is carried;

a step of carrying said recording medium based on said carry command value that has been changed; and

a step of recording on said recording medium that has been carried.

2.(original): A recording method according to claim 1,

wherein said carry command value is changed based on an aggregate carry amount that corresponds to a change in said state of bending.

3.(original): A recording method according to claim 1,

wherein said carry command value is changed when a front end region of said recording medium is carried and when a rear end region of said recording medium is carried.

4.(original): A recording method according to claim 3,

wherein when said front end region is carried, said carry command value is changed to a larger carry command value than when said rear end region is carried.

5.(original): A recording method according to claim 1,

wherein said carry command value is changed according to an attribute of said recording medium.

6.(original): A recording method according to claim 5,

wherein an attribute of said recording medium is a thickness of said recording medium.

7.(original): A recording method according to claim 5,

wherein an attribute of said recoding medium is a length of said recording medium.

8.(original): A recording method according to claim 5,

wherein an attribute of said recoding medium is a width of said recording medium.

9.(original): A recording method according to claim 5,

wherein an attribute of said recoding medium is a material of said recording medium.

10.(original): A recording method according to claim 5,
wherein said carry command value is set according to
a predetermined reference carry command value, and
a correction value for said reference carry command
value, said correction value being associated in a data
table with
an aggregate carry amount of said recording
medium and
an attribute of said recording medium.

11.(original): A recording method according to claim 10,
wherein said data table is set for every predetermined
carry amount of said recording medium.

12.(original): A recording method comprising:
a step of changing a carry command value when carrying a
front end region of a recording medium and when carrying a rear
end region of said recording medium, based on
a predetermined reference carry command value, and
a data table indicating correction values for said
predetermined reference carry command value, said
correction values being set in association with a
thickness, a length, a width, and a material of said

recording medium and being set for every predetermined
carry amount of said recording medium;

a step of making a carrying mechanism for carrying said
recording medium carry said recording medium based on said carry
command value that has been changed; and

a step of recording on said recording medium that has been
carried.

13.(original): A computer-readable medium for making a recording
apparatus for recording on a recording medium that is carried by
a carrying mechanism operate, comprising:

a program code for making said recording medium be carried
based on a carry command value;

wherein said carry command value is changed, when said
recording medium is carried, according to a state of bending of
said recording medium that is carried.

14.(original): A recording apparatus for recording on a
recording medium, comprising:

a carrying mechanism for carrying said recording medium,
wherein said carrying mechanism carries said recording medium
based on a carry command value;

wherein said carry command value is changed according to a
state of bending of said recording medium that is carried.

15.(new): A recording method comprising:

a step of changing a carry command value when carrying a front end region of a recording medium and when carrying a rear end region of said recording medium;

a step of making a carrying mechanism for carrying said recording medium carry said recording medium based on said carry command value that has been changed; and

a step of recording on said recording medium that has been carried.

15.(new): A recording method comprising:

a step of changing a carry command value when carrying a front end region of a recording medium and when carrying a rear end region of said recording medium;

a step of making a carrying mechanism for carrying said recording medium carry said recording medium based on said carry command value that has been changed; and

a step of recording on said recording medium that has been carried.